



J-10



Solution	A	B
Material	ABS Plastic	
System Configurations	Processor Intel® Bay Trail-D Celeron™ J1800 Dual Core 2.41GHz Fanless	Intel® Bay Trail-D Celeron™ J1900 Quad Core 2.0GHz Fanless
	Chipset Intel Celeron J1800 SoC integrated	Intel Celeron J1900 SoC integrated
	Storage Device Mini SATA SSD 32GB,64GB,128GB or 2.5" HDD 500GB	
	Memory Single-Channel DDR3×1, 2GB up to 8GB	
	Graphics Intel® HD Graphics	
	BIOS AMI BIOS	
	OS Windows 7, Windows 10, POSReady 7, Linux	
Display	15" with LCD Backlight (1024×768)	
	Main Display 300:1 Contrast, 350cd/m² Brightness	PCAP Bezel Free Flat Capacitive Touch (10 points multi touch)
I/O Interfaces	Serial Ports 2	
	USB 4×USB type 2.0, 2×USB type 3.0	
	LPT 1	
	HDMI Not Supported	
	VGA 1	
	DC 1	
	LAN 1×10/100/1000Mbps Ethernet	
	Audio Ports 1xMic-in,1xAudio-out	
Options	Customer Display VFD Type (2×20), Alphabet & Numeric	
	Touch Panel Support 4-Wires Resistive Bezel Free Flat (35,000,000 times touch life, 5ms Response time),PCAP Bezel Free Non-Flat Capacitive Touch	
	MSR Track 1&2&3	
Physical Dimension	Dimension 410*260*430mm (WxDxH)	
	Weight 6.1kg	
	Color Black	
Environment	Power Supply DC 12V, 7A Adaptor	
	Temperature Operating: -10°C to 40°C, Storage: -20°C to 60°C	
	Humidity Operating: 20-80% Humidity, Storage: 20-90%	
	Certifications CE, FCC, RoHS, CCC	